

Reddi-Strip® Stapler

Operating and Maintenance

over minimum 1½” thick foamboard

- Use S5RE-16 Reddi-Strip® Staples only.
- Performs best on pink or blue open cell foamboard.

over 1” foamboard or insulating tarp

- Use S5RE-13 Reddi-Strip® Staples only.
 - Performs best on open cell foamboard or tarp over dirt.
 - Will not function on tarp placed directly over slab.
- Will not fasten oversized 5/8” PEX tubing (O.D. exceeding 3/4”).
 - Keep the Reddi-Strip® Stapler loaded to minimum feed line to assure proper feed into tool.
 - Positioning the Reddi-Strip® Stapler with the magazine facing away from the installer further assists proper feed into tool.
 - Recommended spacing: 9” to 12” on straight runs, 6” around bends.
 - The periodic application of a lightweight lubricant into the chute opening around the plunging handle will keep the tool clean and working smoothly.

Comments? Suggestions? If you have any questions about the operation of the Reddi-Strip® Stapler or its applications, please call us during business hours, Monday - Friday 8:00 am to 5:00 pm (Mountain Time) and we'll be happy to help!

 ***Peter Mangone, Inc.***
PLUMBING PRODUCTS DIVISION

800-338-2448 • mail@petermangone.com • www.petermangone.com